

Phone. +61 2 4330 5315

Email. [sales@saintproducts.com.au](mailto:sales@saintproducts.com.au)

3/3 Pioneer Avenue

Tuggerah, NSW 2259, Australia

[www.saintproducts.com.au](http://www.saintproducts.com.au)

# SAINT

Est. Since 1946

# PRODUCT CATALOGUE

Version 1.2



# Table of Contents

<b>About Saint Products</b>	3
<b>Marine Products</b>	5
Bow Ends	6
Knuckles	7
Deck Mounts	9
Joiners	11
Side Mounts	12
Bow Stay Clips	12
Rigging	13
Thumb Screws	14
Fishing	15
Radar Towers	15
Tonneau Fittings	16
Tonneau Loops	17
Buckles	19
Cleats	20
Ladders	20
2 Bow Canopy Kits	21
3 Bow Canopy Kits	22
Anchors	23
Bollards	25
Hatches & Hinges	25
Steering Wheels	25
Filler Caps 38mm	26
Filler Caps 50mm	26
Miscellaneous	27

## About Saint Products

# SAINT

Est. Since 1946

“ SAINT Products is now in its fourth generation, and comprises three main divisions. SAINT Products, Saint Camping and Saint Automotive. Our company is proudly Australian owned and operated. ”

SAINT Products is now in its fourth generation, and continues to expand into new areas. Our company is proudly Australian owned and operated.

Saint Fittings are designed in house, and currently distributes throughout Australia, New Zealand, the Asia Pacific region, North America and parts of the EU.







## Ordering

You are able to place an order by calling us on +61 2 4587 7457 office or visiting our secure online store:  
[www.saintproducts.com.au](http://www.saintproducts.com.au)



## Freight & Delivery

### Domestic Shipping

We use many different couriers and will always strive to deliver your goods in the fastest and cheapest way possible.

### International Shipping

We will delivery anywhere in the world. Just contact us for a quotation.



## Returns

SAINT Products is not required to provide a refund or replacement if you change your mind. However, if you find one of our products to be defective, or significantly different to the image shown on our website, then we will happily replace the product or provide you with a full refund of the cost of the returned goods. The goods are to be returned to SAINT Products at the customers own cost, prior to the refund being given. If the product deemed to be defective is repairable, we will happily repair it without delay.

It is also a condition of sale, that all goods are not subjected to excessive and unreasonable loads and applications. All nylon products are made to withstand ultraviolet light, however over an extended period of time, these goods will fade and/ or discolour. All stainless steel items are also to be maintained by the customer to ensure they do not tea-stain after extended periods in close proximity to salt water.



## Customer Satisfaction

We will always strive to provide you with a timely and reliable service that meets our service standards. We will always provide you with accurate and consistent information and options for your needs. And we will always treat you fairly, with respect and courtesy. Your feedback is always appreciated, whether compliments, suggestions or complaints. What you tell us can help improve our services and products, or correct a problem we may not have been aware of. Please contact us through our website or email us [saint.jonathan@saintproducts.com.au](mailto:saint.jonathan@saintproducts.com.au) and we will respond to your comments promptly.



## Privacy

SAINT Products is committed to maintaining your privacy as required by the Privacy and Personal Information Protection Act 1998 (NSW). We will not collect any more information than in necessary for us to fulfil your requests, nor will we disclose your personal information to anyone without your consent. SAINT Products will never give your personal details to anyone!

[saintmarineproducts.com.au](http://saintmarineproducts.com.au) is a secure site. Additional measures have been put in place when creating this website to ensure the security of our customers credit card and personal information.



## Abbreviations Used Throughout this Catalogue

W = Width

D = Diameter L = Length

H = Height



# Marine Products

Fittings you can trust. Engineered to last.

**SAINT**  
Marine

Est. Since 1946



**Marine Products**

**Bow Ends**

**S200B**

Suits 20.0mm O.D. x 1.6mm wall thickness aluminium tube  
 Material: UV stabilised Nylon 6  
 Colour: Black  
 Centre hole in blade designed to suit 1/4" or M6 screw


**S200W**

Suits 20.0mm O.D. x 1.6mm wall thickness aluminium tube  
 Material: UV stabilised Nylon 6  
 Colour: White  
 Centre hole in blade designed to suit 1/4" or M6 screw


**S204**

Suits 22.2mm (7/8") O.D. x 1.6mm wall thickness stainless steel tube  
 Material: 316 grade stainless steel  
 Centre hole in blade designed to suit 1/4" or M6 screw


**S205**

Suits 25.4mm (1") O.D. x 1.6mm wall thickness stainless steel tube  
 Material: 316 grade stainless steel  
 Centre hole in blade designed to suit 1/4" or M6 screw


**S207**

Suits 31.8mm (1 1/2") O.D. x 1.6mm wall thickness stainless steel tube  
 Material: 316 grade stainless steel  
 Centre hole in blade designed to suit 5/16" or M8 screw


**S208B**

Suits 25.0mm O.D. x 3.0mm wall thickness aluminium tube (19.0mm I.D.)  
 Material: UV stabilised Nylon 6  
 Colour: Black  
 Centre hole in blade designed to suit 1/4" or M6 screw


**S208W**

Suits 25.0mm O.D. x 3.0mm wall thickness aluminium tube (19.0mm I.D.)  
 Material: UV stabilised Nylon 6  
 Colour: White  
 Centre hole in blade designed to suit 1/4" or M6 screw


**S209B**

Suits 25.0 O.D. x 1.6mm wall thickness aluminium tube (21.8mm I.D.)  
 Material: UV stabilised Nylon 6  
 Colour: Black  
 Centre hole in blade designed to suit 1/4" or M6 screw


**S209W**

Suits 25.0mm O.D. x 1.6mm wall thickness aluminium tube (21.8mm I.D.)  
 Material: UV stabilised Nylon 6  
 Colour: White  
 Centre hole in blade designed to suit 1/4" or M6 screw


**S210**

Material: UV stabilised Nylon 6  
 Colour: Black  
 Designed to suit 25.4mm or 25.0mm O.D. x 1.6mm wall thickness tube to reduce the I.D. to 19.0mm.  
 Ideal for using with a S204 stainless steel Bow End (internal) in 25.0mm x 1.6mm aluminium tube, thus creating a barrier from corrosion when mixing S.S. and Aluminium.


**S215**

Suits 31.8mm (1 1/2") O.D. x 1.6mm wall thickness stainless steel tube  
 External Style – secures with 2 x grub screws  
 Material: 316 grade stainless steel  
 Centre hole in blade designed to suit 5/16" or M8 screw


**S217**

Suits 31.8mm (1 1/2") O.D. x 1.6mm wall thickness stainless steel tube  
 External Style – secures with 1 x grub screw  
 Material: 316 grade stainless steel  
 Centre hole in blade designed to suit 1/4" or M6 screw



**Marine Products**

**Bow Ends Cont'd**

**S219**

Suits 38.1mm O.D. x 1.6mm wall thickness aluminium tube  
Material: UV stabilised Nylon 6  
Colour: Black  
Centre hole in blade designed to suit 1/4" or M6 screw


**S215-G**

Suits 25.4mm (1 1/8") O.D. x 1.6mm wall thickness stainless steel tube  
External Style – secures with 2 x grub screws  
Material: 316 grade stainless steel  
Colour: Gold  
Centre hole in blade designed to suit 5/16" or M8 screw


**S217-G**

Suits 31.8mm (1") O.D. x 1.6mm wall thickness stainless steel tube  
External Style – secures with 1 x grub screw  
Material: 316 grade stainless steel  
Colour: Gold  
Centre hole in blade designed to suit 1/4" or M6 screw


**S219-G**

Suits 38.1mm O.D. x 1.6mm wall thickness aluminium tube  
Material: UV stabilised Nylon 6  
Colour: Gold  
Centre hole in blade designed to suit 1/4" or M6 screw


**S325B**

Suits 25.0mm O.D. x 3.0mm wall thickness aluminium tube  
Material: UV stabilised nylon 6  
Colour: Black  
Contains 1/4" UNC captive hex nut  
Helps secure two poles at a 90 degree connection


**S326B**

Suits 25.0mm O.D. x 1.6mm wall thickness aluminium tube  
Material: UV stabilised nylon 6  
Colour: Black  
Contains 1/4" UNC captive hex nut  
Helps secure two poles at a 90 degree connection


**S325W**

Suits 25.0mm O.D. x 3.0mm wall thickness aluminium tube  
Material: UV stabilised nylon 6  
Colour: White  
Contains 1/4" UNC captive hex nut  
Helps secure two poles at a 90 degree connection


**S326W**

Suits 25.0mm O.D. x 1.6mm wall thickness aluminium tube  
Material: UV stabilised nylon 6  
Colour: White  
Contains 1/4" UNC captive hex nut  
Helps secure two poles at a 90 degree connection

**Knuckles**

**S220B**

Suits 20.0mm O.D. aluminium tube  
Style: Tapped Nylon Thread  
Material: UV stabilised Nylon 6  
Colour: Black  
Comes with a 7/8" long combination mush head 304 s/s screw x 1/4" UNC thread


**S220W**

Suits 20.0mm O.D. aluminium tube  
Style: Tapped Nylon Thread  
Material: UV stabilised Nylon 6  
Colour: White  
Comes with a 7/8" long combination mush head 304 s/s screw


**S221B**

Suits 19.0mm O.D. aluminium tube  
Style: Tapped Nylon Thread  
Material: UV stabilised Nylon 6  
Colour: Black  
Comes with a 7/8" long combination mush head 304 s/s screw x 1/4" UNC thread


**S221W**

Suits 19.0mm O.D. aluminium tube  
Style: Tapped Nylon Thread  
Material: UV stabilised Nylon 6  
Colour: White  
Comes with a 7/8" long combination mush head 304 s/s screw x 1/4" UNC thread

**Marine Products**

**Knuckles Cont'd**

**S224**

Suits 22.2mm (7/8") O.D. stainless steel tube

Style: Non-hinged fitting, secures to tube with grub screw

Material: 316 grade stainless steel

Comes with a 7/8" long combination mush head 304 s/s screw x 1/4" UNC thread and a 1/4" UNC grub screw


**S225**

Suits 25.4mm (1") O.D. stainless steel tube

Style: Non-hinged fitting, secures to tube with grub screw

Material: 316 grade stainless steel

Comes with a 1" long combination mush head 304 s/s screw x 1/4" UNC thread and a 1/4" UNC grub screw


**S227**

Suits 31.8mm (1 1/8") O.D. stainless steel tube

Style: Non-hinged fitting, secures to tube with 2 x grub screws

Material: 316 grade stainless steel

Comes with an M8 socket head screw and 2 x M6 grub screw


**S228B**

Suits 22.0mm O.D. aluminium tube

Style: Captive Nut Thread

Material: UV stabilised Nylon 6

Colour: Black

Comes with a 1" long combination mush head 304 s/s screw x 1/4" UNC thread and a captive 1/4" UNC 304 s/s hex nut


**S228W**

Suits 22.0mm O.D. aluminium tube

Style: Captive Nut Thread

Material: UV stabilised Nylon 6

Colour: White

Comes with a 1" long combination mush head 304 s/s screw x 1/4" UNC thread and a captive 1/4" UNC 304 s/s hex nut


**S229B**

Suits 25.0mm O.D. aluminium tube

Style: Captive Nut Thread

Material: UV stabilised Nylon 6

Colour: Black

Comes with a 1" long combination mush head 304 s/s screw x 1/4" UNC thread and a captive 1/4" UNC 304 s/s hex nut


**S229W**

Suits 25.0mm O.D. aluminium tube

Style: Captive Nut Thread

Material: UV stabilised Nylon 6

Colour: White

Comes with a 1" long combination mush head 304 s/s screw x 1/4" UNC thread and a captive 1/4" UNC 304 s/s hex nut


**S230**

Suits 25.4mm (1") O.D. stainless steel tube

Material: 316 grade stainless steel

Hinged variety

Hardware: Comes with an M6 socket head screw which clamps the fitting onto the tube and a 1/4" UNC combination mush head screw which secures the bow end


**S232**

Suits 31.8mm (1 1/8") O.D. stainless steel tube

Material: 316 grade stainless steel

Hinged variety

Hardware: Comes with an M6 socket head screw which clamps the fitting onto the tube and an M8 socket head screw which secures the bow end


**S238**

Suits 38.1mm (1 1/2") O.D. stainless steel tube

Material: 316 grade stainless steel

Hinged variety

Hardware: Comes with two M6 socket head screws which clamp the fitting onto the tube and an M8 socket head screw which secures the bow end


**S257**

Designed to suit 25.4mm O.D. stainless steel tube

Material: 316 grade stainless steel

Comes with 2 x 5/16" screws securing fitting to the tube and 1 x 1/4" UNC combination mush head screw


**S800B**

Suits 22.0mm O.D. aluminium tube

Style: Tapped Nylon Thread

Material: UV stabilised Nylon 6

Colour: Black

Comes with a 1" long combination mush head 304 s/s screw x 1/4" UNC thread



**Marine Products**

**Knuckles Cont'd**

**S801B**

Suits 25.0mm O.D. aluminium tube  
 Style: Tapped Nylon Thread  
 Material: UV stabilised Nylon 6  
 Colour: Black  
 Comes with a 1" long combination  
 mush head 304 s/s screw x 1/4"  
 UNC thread


**S801W**

Suits 25.0mm O.D. aluminium tube  
 Style: Tapped Nylon Thread  
 Material: UV stabilised Nylon 6  
 Colour: White  
 Comes with a 1" long combination  
 mush head 304 s/s screw x 1/4"  
 UNC thread


**S230-G**

Suits 25.4mm (1") O.D. stainless  
 steel tube  
 Material: 316 grade stainless steel  
 Colour: Gold  
 Hinged variety  
 Hardware: Comes with an M6  
 socket head screw which clamps  
 the fitting onto the tube and a  
 1/4" UNC combination mush head  
 screw which secures the bow end


**S232-G**

Suits 31.8mm (1 1/8") O.D. stainless  
 steel tube  
 Material: 316 grade stainless steel  
 Colour: Gold  
 Hinged variety  
 Hardware: Comes with an M6  
 socket head screw which clamps  
 the fitting onto the tube and an M8  
 socket head screw which secures  
 the bow end


**S238-G**

Suits 38.1mm (1 1/2") O.D. stainless  
 steel tube  
 Material: 316 grade stainless steel  
 Colour: Gold  
 Hinged variety  
 Hardware: Comes with two M6  
 socket head screws which clamp  
 the fitting onto the tube and an M8  
 socket head screw which secures  
 the bow end


**S234B**

Suits 32.0mm O.D. aluminium tube  
 Style: Tapped Nylon Thread  
 Material: UV stabilised Nylon 6  
 Colour: Black  
 Comes with a 1" long combination  
 mush head 304 s/s screw x 1/4"  
 UNC thread

**Deck Mounts**

**S250B**

Material: UV stabilised nylon 6  
 Colour: Black  
 Style: Tapped nylon thread  
 Flat Base  
 Comes with a 3/4" long  
 combination mush head 304 s/s  
 screw x 1/4" UNC thread


**S250W**

Material: UV stabilised nylon 6  
 Colour: White  
 Style: Tapped nylon thread  
 Flat Base  
 Comes with a 3/4" long  
 combination mush head 304 s/s  
 screw x 1/4" UNC thread


**S252**

Material: 316 grade stainless steel  
 Style: Tapped thread  
 5 degree angled base  
 Comes with a 3/4" long  
 combination mush head 304 s/s  
 screw x 1/4" UNC thread


**S2531B**

Material: UV stabilised nylon 6  
 Colour: Black  
 Designed to suit nylon deck  
 mounts  
 Secures into place with centre lip  
 which clips into cavity in nylon  
 deck mounts

**Marine Products**

**Deck Mounts Cont'd**

**S2531W**

Material: UV stabilised nylon 6  
 Colour: White  
 Designed to suit nylon deck mounts  
 Secures into place with centre lip which clips into cavity in nylon deck mounts


**S2532B**

Material: UV stabilised nylon 6  
 Colour: Black  
 Designed to suit nylon deck mounts  
 Secures into place with centre lip which clips into cavity in nylon deck mounts


**S2532W**

Material: UV stabilised nylon 6  
 Colour: White  
 Designed to suit nylon deck mounts  
 Secures into place with centre lip which clips into cavity in nylon deck mounts


**S253B**

Material: UV stabilised nylon 6  
 Colour: Black  
 Style: captive s/s nut  
 Flat Base  
 Comes with a 3/4" long combination mush head 304 s/s screw x 1/4" UNC thread and captive 1/4" UNC hex nut


**S253W**

Material: UV stabilised nylon 6  
 Colour: White  
 Style: captive s/s nut  
 Flat Base  
 Comes with a 3/4" long combination mush head 304 s/s screw x 1/4" UNC thread and captive 1/4" UNC hex nut


**S254B**

Material: UV stabilised nylon 6  
 Colour: Black  
 Rotates 180 degree on single line axis  
 Comes with a 7/8" combination mush head 304 s/s screw


**S254W**

Material: UV stabilised nylon 6  
 Colour: White  
 Rotates 180 degree on single line axis  
 Comes with a 7/8" combination mush head 304 s/s screw


**S255**

Large Style Deck Mount  
 Material: 316 grade stainless steel  
 Comes with an M8 screw  
 Four mounting holes on base


**S256**

Material: 316 grade stainless steel  
 Style: Quick release pin secured with lanyard  
 Flat base  
 Same centre to centre base as S252 and all SAINT medium deck mounts


**S258**

Rotates 360 degree and is secured to base with a S440 Quick Release Pin  
 Comes with a 1/4" UNC combination mush head screw which holds bow end to fitting  
 Has same mounting holes (centre to centre) of all medium and small deck mounts  
 Material: 316 grade stainless steel


**S252-G**

Material: 316 grade stainless steel  
 Style: Tapped thread  
 Colour: Gold  
 5 degree angled base  
 Comes with a 3/4" long combination mush head 304 s/s screw x 1/4" UNC thread


**S255-G**

Large Style Deck Mount  
 Material: 316 grade stainless steel  
 Colour: Gold  
 Comes with an M8 screw  
 Four mounting holes on base

**Marine Products**

**Deck Mounts Cont'd**

**S810B**

Material: UV Stabilised Nylon 6  
 Colour: Black  
 Style: Tapped nylon thread  
 Flat Base  
 Comes with a 3/4" long x 1/2" UNC combination mush head screw


**S810W**

Material: UV Stabilised Nylon 6  
 Colour: White  
 Style: Tapped nylon thread  
 Flat Base  
 Comes with a 3/4" long x 1/2" UNC combination mush head screw

**Joiners**

**S280**

Suits 20.0mm O.D. x 1.6mm wall thickness aluminium tube  
 105mm in length and 3mm thick  
 Made from round extruded tube  
 Colour: clear anodised


**S283**

Suits 22.0mm O.D. x 1.6mm wall thickness aluminium tube  
 120mm in length  
 Made from machined solid aluminium bar  
 Colour: bright silver anodised


**S284**

Suits 25.0mm O.D. x 3mm wall thickness aluminium tube  
 120mm in length  
 Made from machined solid aluminium bar  
 Colour: bright silver anodised


**S285**

Suits 25.4mm (1") O.D. x 1.6mm wall thickness stainless steel tube  
 120mm in length  
 Material: 316 grade stainless steel


**S286**

Suits 25.0mm O.D. x 1.6mm wall thickness aluminium tube  
 120mm in length and 3mm thick  
 Made from round extruded tube  
 Colour: bright silver anodised


**S287**

Suits 31.8mm (1 1/4") O.D. x 1.6mm wall thickness stainless steel tube (I.D. 28.30mm dia)  
 Material: 316 grade stainless steel  
 120mm in length  
 Machined from solid tube with central placed shoulder


**S289**

Suits 38.1mm (1 1/2") O.D. x 1.6mm wall thickness stainless steel tube  
 Material: 316 grade stainless steel  
 120mm in length  
 Machined from solid bar and central placed shoulder


**S291**

Suits 25.0mm O.D. x 1.6mm wall thickness aluminium tube  
 2000mm (2.0 metres) in length and 3mm thick  
 Made from round extruded tube  
 Colour: bright silver anodised



**Marine Products**


## Side Mounts


**S260**

Material: 316 grade stainless steel  
Comes with a 7/8" long combination mush head screw x 1/4" UNC thread


**S261B**

Style: captive s/s nut  
Colour: Black  
Material: UV stabilised nylon 6  
Comes with 7/8" long combination mush head screw x 1/4" UNC thread and a 1/4" UNC hex nut


**S261W**

Style: captive s/s nut  
Colour: White  
Material: UV stabilised nylon 6  
Comes with 7/8" long combination mush head screw x 1/4" UNC thread and a 1/4" UNC hex nut


**S262**

Material: 316 grade stainless steel  
Comes with a 5/16" hex head 304 stainless steel screw

## Bow Stay Clips


**S320B**

Suits 20.0mm O.D. x 1.6mm wall thickness aluminium tube  
Material: UV stabilised nylon 6  
Colour: Black


**S320W**

Suits 20.0mm O.D. x 1.6mm wall thickness aluminium tube  
Material: UV stabilised nylon 6  
Colour: White


**S322B**

Suits 19.0mm O.D. x 1.6mm wall thickness aluminium tube  
Material: UV stabilised nylon 6  
Colour: Black


**S324B**

Suits 22.0mm O.D. x 1.6mm wall thickness aluminium tube  
Material: UV stabilised nylon 6  
Colour: Black


**S324B-Short**

Suits 22.0mm O.D. x 1.6mm wall thickness aluminium tube  
Material: UV stabilised nylon 6  
Colour: Black

**Marine Products**

**Rigging**

**S301**

Suits 25.0mm fabric strap  
Material: 5.0mm dia. O.D. 316 grade stainless steel rod  
Ends welded together for additional strength


**S303**

Material: 5.0mm dia. O.D. 316 grade stainless steel rod


**S303a**

Material: 6.0mm dia. O.D. 316 grade stainless steel rod  
Dimensions: mounting holes (centre to centre) 47mm apart


**S360**

To suit 25.0mm fabric strap  
Material: Nickle Plated steel  
Ends welded together for additional strength  
Dimensions: 32.0mm outside width x 26.0mm total height x 3mm dia rod.


**S361**

To suit 25.0mm fabric strap  
Material: 316 grade stainless steel;  
Ends welded together for additional strength  
Dimensions: 38.0mm outside width x 28.0mm total height x 4mm dia rod.


**S364**

To suit 25.0mm fabric strap  
Material: Nickle Plated steel  
Ends welded together for additional strength  
Dimensions: 40.0mm outside width x 30.0mm total height x 5mm dia rod.


**S365**

To suit 25.0mm fabric strap  
Material: 316 grade stainless steel  
Ends welded together for additional strength  
Dimensions: 38.0mm outside width x 32.0mm total height x 5mm dia rod.


**S366**

To suit 50.0mm fabric strap  
Material: Nickle Plated steel  
Ends welded together for additional strength  
Dimensions: 63.0mm outside width x 58.0mm total height x 6mm dia rod.


**S368**

To suit 50.0 mm fabric strap  
Material: 316 grade stainless steel  
Ends welded together for additional strength  
Dimensions: 63.0mm outside width x 58.0mm total height x 6mm dia rod.


**SSPE-1**

Square Eye Pad – Small made from 316 grade stainless steel  
Dimensions:  
30mm wide x 35mm long  
21mm high  
2.5mm thick plate  
5mm Ring width


**SSPE-2**

Square Eye Pad – Medium made from 316 grade stainless steel  
Dimensions:  
35mm wide x 40mm long  
26mm high  
2.5mm thick plate  
6mm Ring width


**SSPE-3**

Square Eye Pad – Large made from 316 grade stainless steel  
Dimensions:  
40mm wide x 50mm long  
32mm high  
3mm thick plate  
8mm Ring width

**Marine Products**


## Thumb Screws


**S310B**

Material: UV stabilised nylon 6 with 1/4" UNC thread screw 25mm (1") long

Suits all nylon Knuckles and Deck Mounts

Colour: Black


**S310W**

Material: UV stabilised nylon 6 with 1/4" UNC thread screw 25mm (1") long

Suits all nylon Knuckles and Deck Mounts

Colour: White


**S311B**

Material: UV stabilised nylon 6 with 1/4" UNC thread screw 20mm long

Suits all nylon Knuckles and Deck Mounts

Colour: Black


**S315B**

Material: UV stabilised nylon 6 with 1/4" UNC thread screw 25mm (1") long

Suits all nylon Knuckles and Deck Mounts

Colour: Black


**S315W**

Material: UV stabilised nylon 6 with 1/4" UNC thread screw 25mm (1") long

Suits all nylon Knuckles and Deck Mounts

Colour: White


**S315R**

Same as the S315B style with a red nylon plastic head. 1/4" UNC Thread. Please note SAINT can manufacture any colour thumb screw you like. Please contact us for other colour choices and options.


**S316B**

Material: UV stabilised nylon 6 with M6 screw 25mm (1") long

Not designed for nylon fittings. Special M6 thread.

Colour: Black


**S317**

M8 Screw x 1" long


**S318**

2" Long x 1/4" UNC Thread Thumb Screw. Same as the S315B Style but with a longer screw for additional applications.



Marine Products



## Fishing



### S340B


To suit 25.0mm O.D. aluminium tube

Designed to hold two poles parallel, 55.0mm apart (centre to centre).

89mm long x 30mm wide x 34mm high

Material: Extruded aluminium section

Colour: Black powder coated



### S340C

To suit 25.0mm O.D. aluminium tube

Designed to hold two poles parallel, 55.0mm apart (centre to centre).

89mm long x 30mm wide x 34mm high

Material: Extruded aluminium section

Colour: Bright silver anodised



### S342B


To suit 25.0mm O.D. aluminium tube

Designed to hold two poles parallel, 55.0mm apart (centre to centre).

89mm long x 50mm wide x 34mm high

Material: Extruded aluminium section

Colour: Bright silver anodised



### S342C

To suit 25.0mm O.D. aluminium tube

Designed to hold two poles parallel, 55.0mm apart (centre to centre).

89mm long x 50mm wide x 34mm high



### S346

Suits 25.0mm O.D. aluminium tube

Designed to suit 40mm fishing rod handles

Material: Aluminium

Colour: Bright silver anodised



Product Code	Product Description
S347	All angle adjustable rod holder - 316 SS - 230mm long
S347A	All angle adjustable rod holder - 316 SS - 290mm long
S348	Clamp on adjustable rod holder - 316 SS
S349	Flush mount rod holder - 316 SS
S355	Rack mount rod holder - 4 tubes - 316 SS

## Radar Towers



### S760

Designed to suit Simrad brand.  
Made from 316 grade stainless steel.



### S764

Designed to suit Simrad brand.  
Made from Aluminium and white powder coated.

**Marine Products**

**Tonneau Fittings**

**S305B**

Suits up to 6mm shock cord  
Two mounting holes which accept 5mm rivet/fastener  
Dimensions: 40mm long x 24mm wide x 14mm high  
Material: UV stabilised nylon 6  
Colour: Black


**S305C**

Lashing Hook  
Chrome plated ABS plastic


**S305W**

Suits up to 6mm shock cord  
Two mounting holes which accept 5mm rivet/fastener  
Dimensions: 40mm long x 24mm wide x 14mm high  
Material: UV stabilised nylon 6  
Colour: White


**S308B**

Suits up to 8mm shock cord  
Accepts up to 4.8mm rivet/fastener  
Dimensions: 18mm width x 15mm height  
Material: UV stabilised nylon 6  
Colour: Black


**S308B-D**

Suits up to 8mm shock cord  
Accepts up to 4.8mm rivet/fastener  
Dimensions: 18mm width x 15mm height  
Material: PP  
Colour: Black


**S308B-T**

Suits up to 5mm shock cord  
Accepts up to 4mm rivet/fastener  
Dimensions: 17mm width x 12mm height  
Material: UV stabilised nylon 6  
Colour: Black


**S308C**

Tonneau Button  
Chrome plated ABS plastic


**S308SS**

Suits up to 8mm shock cord  
Accepts up to 4.8mm rivet/fastener  
Dimensions: 18mm width x 15mm height  
Material: 316 grade stainless steel


**S308W**

Suits up to 8mm shock cord  
Accepts up to 4.8mm rivet/fastener  
Dimensions: 18mm width x 15mm height  
Material: UV stabilised nylon 6  
Colour: Black


**S632**

Elastic Clip  
Suits: 6mm cord  
Material: UV stabilised nylon 6  
Colour: Black


**S634**

Elastic Clip  
Suits: 8mm cord  
Material: UV stabilised nylon 6  
Colour: Black

**Marine Products**



# **Tonneau Loops**



## **S600B**

50mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia.

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body head through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. fastener

Colour: Black only



## **S601B**

70mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state

Also known as a "130"

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body head through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. fastener

Colour: Black



## **S601W**

70mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state

Also known as a "130"

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body head through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. fastener

Colour: White



## **S602B**

80mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state

Also known as a "150"

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body head through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. fastener

Colour: Black



## **S602W**

80mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state

Also known as a "150"

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body head through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. fastener

Colour: White



## **S603B**

90mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state

Also known as a "170"

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body head through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. fastener

Colour: Black



## **S603W**

90mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state

Also known as a "170"

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body head through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. fastener

Colour: White



## **S604B**

100mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state

Also known as a "190"

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body head through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. fastener

Colour: Black



**Marine Products**

**Tonneau Loops Cont'd**

**S604W**

100mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state  
Also known as a "190"

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body head through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. fastener

Colour: White


**S605B**

110mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state  
Also known as a "209"

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body head through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. fastener

Colour: Black


**S605W**

110mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state  
Also known as a "209"

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia.

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. Fastener

Colour: White


**S606B**

130mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia.

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. Fastener

Colour: Black only


**S607B**

100mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state  
Also known as a "190"

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body head through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. fastener

Colour: Black


**S609B**

210mm long

Length measured from centre of mounting hole in plastic head to end of elastic cord in relaxed state

Material: UV stabilised nylon 6 and woven fabric covered elastic cord 6mm in dia

Elastic cord is secured using a 316 stainless steel clip and sealed into nylon body head through ultrasonic process.

Comes with a nylon button which covers the 4mm dia. fastener

Colour: Black


**S610**

High Tensile Steel – heat treated for extended durability  
Helps secure the durable fastener to the tonneau loop body head  
Can be used with a "G" clamp or other hardware


**S605-T**

"Tiger Loop" – Modelled on the S605 110mm long tonneau loop with a combination yellow and black mixed elastic thread with moulded black head. Please note that SAINT can manufacture any colour tonneau loop thread with a combination of any tonneau plastic head. Create a mix of colours and styles to suit any situation. Just let us know your requirements for an easy, quick quotation.

**Marine Products**

**Tonneau Loops Cont'd**

**S615-O**

Tonneau Loop 8mm in Orange Colour cord, no moulded head. SAINT can supply any elastic cord thickness, length and colour. With the option of a moulded head or a bare 316 metal clip if the loop is to be secured with a non visible head. Please contact us for any further information about available colours, styles etc.


**S611**

High Tensile Steel – heat treated for extended durability  
Helps secure the durable fastener to the tonneau loop body head  
Can be used with a "G" clamp or other hardware


**S620**

Quick Fastening and Releasing Elastic Rope System (pack of 4)  
Uses 5mm elastic cord 75mm long  
Colour: Blue toggle and white cord with blue stripes


**S630B**

Quick Fastening and releasing Elastic Rope System  
Plastic head only – accepts 5mm cord  
Colour: Black


**S631B**

Woven fabric covered elastic cord – 5mm dia.  
75mm in length

**Buckles**

**S300B**

Material: UV stabilised nylon 6  
Colour: Black  
Designed to suit 25mm fabric


**S300W**

Material: UV stabilised nylon 6  
Colour: White  
Designed to suit 25mm fabric


**S302B**

Material: UV stabilised nylon 6  
Colour: Black  
Designed to suit 25mm fabric


**S306**

Material: 316 grade stainless steel  
Designed to suit 25mm fabric  
Slight curve across width

Marine Products



Cleats



S370

Material: 316 grade stainless steel



S372

Material: 316 grade stainless steel



S373

Material: 316 grade stainless steel



S374

Material: 316 grade stainless steel



S375

Material: 316 grade stainless steel

Ladders

Telescopic - Dive



Product Code	Production Description
SLTD4	4 step telescopic dive ladder
SLTD3	3 step telescopic dive ladder

Folding




Product Code	Production Description
SLF4	4 step folding ladder
SLF3	3 step folding ladder



**Marine Products**


## 2 Bow Canopy Kits



### S165S

Frame: 25.0mm O.D. x 3.0mm wall thickness Bright Silver anodised aluminium

Comes with camber (roll) across the beam

Number of Bows: 4 x half bows to make 2 Bow Canopy

Dimensions once assembled:


- Beam 2100mm
- Main leg 1200mm and front leg 800mm

Fittings included:

- S208 Bow End (black) x 4
- S229 Knuckle (black) x 2
- S253 Deck Mount (black) x 2
- S283 Joiner x 2

Please note the frame DOES NOT include fabric.

Other alternatives: White fittings can be changed. Also aluminium available in Clear Anodised (dull finish) or Black Powder Coated. Please enquire for availability.



### S167ss

Frame: 25.04mm O.D. x 1.6mm wall thickness 316 grade mirror polished stainless steel round tube

Comes with camber (roll) across the beam

Number of Bows: 4 x half bows to make 2 Bow Canopy


Dimensions once assembled:

- Beam 2100mm
- Main leg 1200mm and front leg 800mm

Fittings included (stainless steel):

- S215 Bow End External x 4
- S225 Knuckle x 2
- S252 Deck Mount x 2
- S.S. Joiner x 2

Please note the frame DOES NOT include fabric.



### S170S

Frame: 25.0mm O.D. x 1.6mm wall thickness Bright Silver anodised aluminium

Comes with camber (roll) across the beam

Number of Bows: 4 x half bows to make 2 Bow Canopy

Dimensions once assembled:


- Beam 1800mm
- Main leg 800mm and front leg 400mm

Fittings included (nylon):

- S209 Bow End (black) x 4
- S229 Knuckle (black) x 2
- S253 Deck Mount (black) x 2
- S286 Joiner x 2

Please note the frame DOES NOT include fabric.

Other alternatives: White fittings can be changed. Also aluminium available in Clear Anodised (dull finish) or Black Powder Coated. Please enquire for availability.



### S172S

Frame: 25.0mm O.D. x 1.6mm wall thickness Bright Silver anodised aluminium

Comes with camber (roll) across the beam

Number of Bows: 4 x half bows to make 2 Bow Canopy


Dimensions once assembled:

- Beam 2100mm
- Main leg 1200mm and front leg 800mm

Fittings included:

- S209 Bow End (black) x 4
- S229 Knuckle (black) x 2
- S253 Deck Mount (black) x 2
- S286 Joiner x 2

Please note the frame DOES NOT include fabric.



### S180ss

Frame: 31.8mm O.D. x 1.6mm wall thickness 316 grade mirror polished stainless steel round tube

Comes with camber (roll) across the beam

Number of Bows: 4 x half bows to make 2 Bow Canopy

Dimensions once assembled:

- Beam 2100mm
- Main leg 1200mm and front leg 800mm


Fittings included (stainless steel):

- S217 Bow End External x 4
- S227 Knuckle x 2
- S255 Deck Mount x 2
- S.S. Joiner x 2

Please note the frame DOES NOT include fabric.

**Marine Products**


## 3 Bow Canopy Kits



### S160S

Frame: 25.0mm O.D. x 1.6mm wall thickness Bright Silver anodised aluminium

Comes with camber (roll) across the beam

Number of Bows: 6 x half bows to make 3 Bow Bimini

Dimensions once assembled:


- Beam 1800mm
- Main leg 800mm, front leg 800mm and middle leg 400mm

Fittings included (nylon):

- S209 Bow End (black) x 6
- S229 Knuckle (black) x 4
- S253 Deck Mount (black) x 2
- S286 Joiner x 3

Please note the frame DOES NOT include fabric.

Other alternatives: White fittings can be changed. Also aluminium available in Clear Anodised (dull finish) or Black Powder Coated. Please enquire for availability.



### S162S

Frame: 25.0mm O.D. x 1.6mm wall thickness Bright Silver anodised aluminium

Comes with camber (roll) across the beam

Number of Bows: 6 x half bows to make 3 Bow Bimini

Dimensions once assembled:


- Beam 2100mm
- Main leg 1200mm, front leg 1200mm and middle leg 700mm

Fittings included (nylon):

- S209 Bow End (black) x 6
- S229 Knuckle (black) x 4
- S253 Deck Mount (black) x 2
- S286 Joiner x 3

Please note the frame DOES NOT include fabric.

Other alternatives: White fittings can be changed. Also aluminium available in Clear Anodised (dull finish) or Black Powder Coated. Please enquire for availability.



### S166S

Frame: 25.0mm O.D. x 3.0mm wall thickness Bright Silver anodised aluminium

Comes with camber (roll) across the beam

Number of Bows: 6 x half bows to make 3 Bow Bimini


Dimensions once assembled:

- Beam 2100mm
- Main leg 1200mm, front leg 1200mm and middle leg 700mm

Fittings included (nylon):

- S208 Bow End (black) x 6
- S229 Knuckle (black) x 4
- S253 Deck Mount (black) x 2
- S284 Joiner x 3

Please note the frame DOES NOT include fabric.



### S168ss

Frame: 31.8mm O.D. x 1.6mm wall thickness 316 grade mirror polished stainless steel round tube

Comes with camber (roll) across the beam

Number of Bows: 6 x half bows to make 3 Bow Bimini


Dimensions once assembled:

- Beam 2100mm
- Main leg 1200mm, front leg 1200mm and middle leg 700mm

Fittings included (S.S.):

- S217 Bow End x 6
- S227 Knuckle x 4
- S255 Deck Mount x 2
- S.S. Joiner x 3

Please note the frame DOES NOT include fabric.



### S181ss

Frame: 31.8mm O.D. x 1.6mm wall thickness 316 grade mirror polished stainless steel round tube

Comes with camber (roll) across the beam

Number of Bows: 6 x half bows to make 3 Bow Bimini

Dimensions once assembled:

- Beam 2100mm
- Main leg 1200mm, front leg 1200mm and middle leg 700mm

Fittings included (S.S.):

- S217 Bow End x 6
- S227 Knuckle x 4
- S255 Deck Mount x 2
- S.S. Joiner x 3

Please note the frame DOES NOT include fabric.



## Anchors

### Claws



Style	Product Code	Weight
Claw	SAC1	1KG
Claw	SAC2	2KG
Claw	SAC3	3KG
Claw	SAC5	5KG
Claw	SAC7.5	7.5KG
Claw	SAC10	10KG
Claw	SAC15	15KG
Claw	SAC20	20KG
Claw	SAC25	25KG
Claw	SAC30	30KG
Claw	SAC40	40KG
Claw	SAC50	50KG
Claw	SAC80	80KG

### Plough



Style	Product Code	Weight
Plough	SAP5	5KG
Plough	SAP7	7KG
Plough	SAP10	10KG
Plough	SAP12	12KG
Plough	SAP15	15KG
Plough	SAP20	20KG
Plough	SAP27	27KG
Plough	SAP35	35KG
Plough	SAP40	40KG
Plough	SAP50	50KG



## Anchors Cont'd

### Grapple



Style	Product Code	Weight
Grapple	SAG700	0.7KG
Grapple	SAG1500	1.5KG
Grapple	SAG2500	2.5KG
Grapple	SAG3500	3.5KG
Grapple	SAG4000	4.0KG
Grapple	SAG5000	5.0KG
Grapple	SAG6000	6.0KG
Grapple	SAG7000	7.0KG
Grapple	SAG8000	8.0KG
Grapple	SAG10000	10.0KG
Grapple	SAG12000	12.0KG

### Delta



Style	Product Code	Weight
Delta	SAD3	3KG
Delta	SAD4	4KG
Delta	SAD5	5KG
Delta	SAD6	6KG
Delta	SAD7	7KG
Delta	SAD8	8KG
Delta	SAD9	9KG
Delta	SAD10	10KG
Delta	SAD15	15KG
Delta	SAD20	20KG
Delta	SAD25	25KG
Delta	SAD30	30KG
Delta	SAD40	40KG
Delta	SAD50	50KG
Delta	SAD60	60KG
Delta	SAD80	80KG
Delta	SAD100	100KG



**Marine Products**

**Bollards**


Product Code	Product Description
SB-1	Angled Cross Bollard 316 SS
SB-2	Split Bollard 316 SS
SB-3	Split Bollard and Locking Pin 316 SS
SB-4	Single Cross Bollard 80 x 80 316 SS
SB-5	Single Cross Bollard 100 x 100 316 SS
SB-6	Single Cross Bollard 135 x 135 316 SS
SB-7	Single Cross Bollard 195 x 150 316 SS
SB-8	Single Cross Bollard 240 x 190 316 SS

**Hatches & Hinges**

**SHH-1**

Hatch Hinge made from 316 grade Stainless Steel.

Four Mounting holes on Door side, and Two on mounting post side

Dimensions: 56mm wide x 75.3mm long. Total height when sitting flat 34mm.


**SSFLR**

Square flush lift ring for hatches. Made from 316 grade Stainless Steel

Four mounting holes.

Dimensions:

62mm long x 44mm wide.

Recess Depth – 12mm

Centre to Centre hole distance – Long 50mm, Wide 31mm

Ring space – 24.3mm

Mounting plate thickness – 3.3mm


**SSCHS**

Silent Cast Square Hinge – made from 316 grade stainless steel

Two mounting holes each side

Dimensions:

50mm wide x 40mm long

Plate Thickness: 5mm

Mounting holes Centre to Centre each side – 20mm

Mounting holes centre to centre across width including hinge mechanism – 32mm


**SSCHR**

Silent Cast Hinge Rectangle

Five Mounting Holes, Two on short side, and Three on long side

Dimensions:

Total Length 85mm x 40mm wide tapering to 32mm wide

Plate 5mm Thick

Mounting holes centre to centre across hinge – 32mm

Mounting holes centre to centre each side – 20mm

**Steering Wheels**

**SSW-1**

Stainless steel round steering wheel.

Made from 316 grade materials. High quality custom made product.

Total width 13.5"

Material: Made from ¾" round SS tube for easy gripping.

Three side spokes coming into a central mounting point.

## Marine Products



## Filler Caps 38mm



Product Code	Product Description
S393W	38mm Water Filler Cap Straight – Lockable with key
S393F	38mm Fuel Filler Cap Straight – Lockable with key
S393G	38mm Waste Filler Cap Straight – Lockable with key
S393D	38mm Diesel Filler Cap Straight – Lockable with key
S395W	38mm Water Filler Cap 45 degree bent – Lockable with key
S395F	38mm Fuel Filler Cap 45 degree bent – Lockable with key
S395G	38mm Waste Filler Cap 45 degree bent – Lockable with key
S395D	38mm Diesel Filler Cap 45 degree bent – Lockable with key



## S390

Material: 316 grade stainless steel  
Dia. 75mm  
Top plate thickness 3mm  
Total length 80mm

## S392

Material: 316 grade stainless steel  
Dia. 75mm  
Top plate thickness 3mm  
Total length 80mm

## Filler Caps 50mm



Product Code	Product Description
S394W	50mm Water Filler Cap Straight – Lockable with key
S394F	50mm Fuel Filler Cap Straight – Lockable with key
S394G	50mm Waste Filler Cap Straight – Lockable with key
S394D	50mm Diesel Filler Cap Straight – Lockable with key
S396W	50mm Water Filler Cap 45 degree bent – Lockable with key
S396G	50mm Waste Filler Cap 45 degree bent – Lockable with key
S396F	50mm Fuel Filler Cap 45 degree bent – Lockable with key
S396D	50mm Diesel Filler Cap 45 degree bent – Lockable with key

**Marine Products**

**Miscellaneous**

**S328B**

Suits 25.0mm O.D. x 1.6mm wall thickness aluminium tube  
 Material: UV stabilised nylon 6  
 Colour: Black  
 Allows two 25.0mm O.D. tube to be connected at a 90 degree point


**S330B**

Suits 20.0mm x 1.6mm wall thickness aluminium tube  
 Comes with two eared thumb screw (S315B) which secures side A to side B through a 1/4" UNC hex nut  
 A slight release in tension of the thumb screw allows the fitting to ratchet to differing positions/angles.  
 The Elbow Joint has multiple centrally located teeth to fasten a desired angle in place.  
 Similar to an Umbrella Joint.  
 Material: UV stabilised nylon 6


**S332**

Suits 25.4mm x 1.6mm wall thickness stainless steel tube  
 Comes with two eared thumb screw (S315B) which secures side A to side B through a 1/4" UNC tapped thread  
 A slight release in tension of the thumb screw allows the fitting to ratchet to differing positions/angles.  
 The Elbow Joint has multiple centrally located teeth to fasten a desired angle in place.  
 Similar to an Umbrella Joint.  
 Material: 316 grade stainless steel


**S350B**

Suits 25.0mm O.D. aluminium tube  
 Designed to secure two poles parallel in a temporary manner  
 Material: UV stabilised nylon 6  
 Colour: Black


**S380**

Material: 316 grade stainless steel  
 Knob head dia. 35mm, Knob head height approx. 24mm  
 Shoulder dia. 16mm, Shoulder height approx. 17mm  
 Screw thread: 5/16" UNC


**S590**

Round 25.0mm O.D. x 1.6mm wall thickness aluminium  
 Colour: Bright Silver anodised  
 Length: 1500 long


**S591**

Round 25.0mm O.D. x 3mm wall thickness aluminium  
 Colour: Bright Silver anodised  
 Length: 1500 long


**S592**

Round 25.4mm (1") O.D. x 1.6mm wall thickness 316 grade mirror polished stainless steel  
 Length: 1500 long


**S593**

Round 31.8mm (1 1/4") O.D. x 1.6mm wall thickness 316 grade mirror polished stainless steel  
 Length: 1500 long


**S594**

Round 38.1mm (1 1/2") O.D. x 1.6mm wall thickness 316 grade mirror polished stainless steel  
 Length: 1500 long


**S382**

Side Release Buckle Straight – 50mm  
 Material: UV stabilised nylon 6  
 Colour: Black


**S383**

Side Release Buckle Curved – 50mm  
 Material: UV stabilised nylon 6  
 Colour: Black

Marine Products



Miscellaneous



**S384**

Side Release Buckle Straight –  
25mm  
Material: UV stabilised nylon 6  
Colour: Black



**S385**

Side Release Buckle Curved –  
25mm  
Material: UV stabilised nylon 6  
Colour: Black



**SAINT**

---

Est. Since 1946





# SAINT

---

Est. Since 1946

**Phone.** +61 2 4330 5315

**Email.** [sales@saintproducts.com.au](mailto:sales@saintproducts.com.au)

3/3 Pioneer Avenue

Tuggerah, NSW 2259, Australia

[www.saintproducts.com.au](http://www.saintproducts.com.au)